XEAST XE-S2 50M / 70M / 100M / 120M□□□□□□□□□□□□

SPECIFICATION

□□	XE-S2	□□&□□; Subtraction	√
□□	0.2□50/70/100 /120□	□□□□□	√
□□	±□2□□+ 5 * 10-5Dmm□	□□□□	□/□□□□□□/□□□
□□□□	√	□□□□	□/□□/□□/□□+□
□□□□	√	□□□□	30□□
□□□□	√	□□□□	2.0□□□□
□□□□	√	□□□□	2□
□□□□□	√	□□□□	□□□□
□□□□□□□□□1□	√	□□□□	3□AA□□□□□□□□□□
□□□□□□□□□2□	√	□□□□	0□40°C
□□□□	√	□□	115 * 49 *26□□
□□□□	√		

PRODUCT PICTURES

49mm
115mm
XEAST
MEAS
MAX/MIN
UNIT
CLEAR
49mm
115mm
CAUTION
26mm
115mm

Dual power mode

This product adopts dual power supply mode, ordinary dry battery and nickel-metal hydride rechargeable battery. When installing rechargeable battery, it can be directly charged. When installing ordinary dry battery, please do not use USB charging to avoid accidents.

Cycle charging

Nickel-metal hydride rechargeable battery

Emergency battery duration

3*dry battery

XEAST®
DON'T
STARE
INTO
BEAM

XEAST®

LASER
2
100m
Shenzhen MiloSeey
Technology co.,LTD
WARNING
DO NOT CHARGE
PRIMARY
BATTERIES

100%
XEAST®
68.8°
2.806 m
6.420 m
8.015 m
26.035 m
MEAS
UNIT
CLEAR

Electronic angle sensor

When measuring, the angle is displayed in real time,
the data is more intuitive, easy to read, and it is easier to find the horizontal direction to meet various measurement requirements.

Terms of Trade

XEAST®

1□□□□□□□
□□□□□□□□□T / T□L / C□Paypal□MoneyGram□□□□□□
□□□30□□□□□□70□□□□
2□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□Express□DHL□TNT□UPS□FEDEX□EMS□SPSR□139 express□□□LCL□FCL□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Company Informations

XEAST®

SALES TEAM
YEAST®
Your Testing Partner
WOKRSHOP