



spécification à Numérique Multimètre XE-608

Specification parameter	Measuring range	Precision
DC voltage	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	±(0.5%+3)
AC voltage	9.999mV/99.99mV/999.9mV/9.999V/99.99V/750.0V	±(1.0%+3)
DC voltage	99.99uA/999.9uA	±(0.8%+3)
	999.9mA/9.999A	±(1.0%+3)
AC voltage	99.99uA/999.9uA	±(1.0%+3)
	999.9mA/9.999A	±(1.2%+3)
Resistance	99.99Ω	±(1.0%+3)
	999.9Ω/9.99ΚΩ/99.99ΚΩ/999.9ΚΩ	±(0.5%+3)
	9.999ΜΩ	±(1.5%+3)
	99.99ΜΩ	±(3.0%+3)
Capacitance	9.999nF	±(5.0%+20)
	99.99nF/999.9nF/9.999uF/99.99uF/999.9uF	±(2.0%+5)
	9.999mF	±(5.0%+5)
Frequency	99.99Hz/999.9Hz/9.999kHz/99.99kHz	±(0.1%+2)
	999.9kHz/9.999MHz	
Duty Cycle	1%-99%	±(0.1%+2)
Measuring Temperature Range	-20°C~1000°C/-4°F~1832°F	±(2.5%+5)
Diode Test	Yes	
Features Features		
Auto range / manual range	True RMS	Date hold
Backlit display	Low battery prompt	auto power-off
Relative value measurement		

PRODUCT PICTURES



Les images de différentes vues de multimètre numérique LCD à notre XE-608









APPLICATIONS



Applications au Digital Multimeter XE-608

Analog bar graph







































BUTTON DESIGN







- 1.Buttotn design, one-handed operation, faster and high efficiency working.
- 100,000 times efficient testing, still work perfect and unaffected by harsh environment.




- Tranditional rotary design, need two-handed operation, effect working efficiency.
- Contact plate is easy get rusty and resulting in poor connecting in wet environment.

ZT-XTHERMOCOUPLE



OTHER THERMOCOUPLES





▲ High quality flexible temperature probe

Panel Introduction



Accurate Measurement, True Reflection






Automatic switch to current testing

Tranditional multimeter must switch to current mode then measure current,ZT-X can automatically switch to current mode when plug in test leads.







▲ After the insertion of the pen







When the test leads are inserted into or some functions are shielded. Then the voltage

will change to current automatically.

When the test leads are inserted into all functions can measure normally.











PACKAGE INCLUDE



Paquet au multimètre numérique XE-608







● TERMS OF TRADE



Termes de l'échange

1). Modalités de paiement:

Nous acceptons T / T, L / C, Paypal, MoneyGram et Western Union.

Dépôt de 30% et autre équilibre de 70% avant l'expédition.

2). Conditions d'expédition:

Cela dépend de la quantité de commande de clients et de votre demande spéciale. Nous adoptons

généralement Express (DHL, TNT, UPS, FEDEX, SME, SPSR, 139 exprès et ainsi de suite), LCL, FCL Les articles seront soigneusement vérifiés avant l'expédition, et nous mettrons à jour le statut de la livraison en temps opportun après l'envoi des marchandises.

COMPANY INFORMATIONS















Your Testing Partner







