SPECIFICATION

XEAST®

□□ □ □□□□ □□□□□□□ **XE-608**

Specification parameter	Measuring range	Precision
DC voltage	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	±(0.5%+3)
AC voltage	9.999mV/99.99mV/999.9mV/9.999V/99.99V/750.0V	±(1.0%+3)
DC voltage	99.99uA/999.9uA	±(0.8%+3)
	999.9mA/9.999A	±(1.0%+3)
AC voltage	99.99uA/999.9uA	±(1.0%+3)
	999.9mA/9.999A	±(1.2%+3)
Resistance	99.99Ω	±(1.0%+3)
	999.9Ω/9.99KΩ/99.99KΩ/999.9KΩ	±(0.5%+3)
	9.999MΩ	±(1.5%+3)
	99.99MΩ	±(3.0%+3)
Capacitance	9.999nF	±(5.0%+20)
	99.99nF/999.9nF/9.999uF/99.99uF/999.9uF	±(2.0%+5)
	9.999mF	±(5.0%+5)
Frequency	99.99Hz/999.9Hz/9.999kHz/99.99kHz	±(0.1%+2)
	999.9kHz/9.999MHz	
Duty Cycle	1%-99%	±(0.1%+2)
Measuring Temperature Range	-20°C~1000°C/-4°F~1832°F	±(2.5%+5)
Diode Test	Yes	
Features		
Auto range / manual range	True RMS	Date hold
Backlit display	Low battery prompt	auto power-off
Relative value measurement		

PRODUCT PICTURES

XEAST®

□□□□**XE-608**□**LCD**□□□□□□□□□□□□□□□□□□□□□□□□□□□□

XEAST®

XEAST® XE-608
9999 COUNTS
AUTO MANU
HOLD PEAK
DC
AC
T-RMS
DCA/ACA
>2S POWER
HOLD
>2S REL
AUTO POWER OFF
NCV
RANGE
Hz%
A mA
TRUE RMS
FUSED
10A MAX
COM
FUSED
200mA MAX
600V CAT III
1000V CAT II
µA

XEAST®

XEAST® XE-608
9999 COUNTS
AUTO MANU Δ
HOLD PEAK MAX MIN
DC
AC
T-RMS
DC/AC/CA
>2S POWER
HOLD
>2S REL
AUTO POWER OFF
RANGE
A mA
TRUE RMS
COM
VΩHz
μA

● APPLICATIONS

XEAST®

□□□□□□□□□□XE-608□□□□

Analog bar graph

BUTTON DESIGN Vs ROTARY DESIGN

- 1.Buttotn design,one-handed operation,faster and high efficiency working.
- 100,000 times efficient testing,still work perfect and unaffected by harsh environment.

- Tranditional rotary design,need two-handed operation,effect working efficiency.
- Contact plate is easy get rusty and resulting in poor connecting in wet environment.

ZT-X THERMOCOUPLE **Vs** OTHER THERMOCOUPLES

▲High quality flexible temperature probe

Panel Introduction

Accurate Measurement , True Reflection

The new desigh button multimeter has a mini size and complete functions

Measure ° C / ° F

Celsius and Fahrenheit display simultaneously

Voltage measurement

Voltage (V) and Frequency(Hz) display simultaneously .

Automatic switch to current testing

Tranditional multimeter must switch to current mode then measure current,ZT-X can automatically switch to current mode when plug in test leads.

▲ Before inserting the pen

▲ After the insertion of the pen

Tips

When the test leads are inserted into or , some functions are shielded. Then the voltage will change to current automatically.

When the test leads are inserted into all functions can measure normally.

Resistance Minimum measurement range 0.01Ω.

● PACKAGE INCLUDE

XEAST®

□□□□□□□□□□□□XE-608□□□□□□□□

● TERMS OF TRADE

XEAST®

□□□□

1□□□□□□□□
□□□T / T□L / C□Paypal□MoneyGram□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□30□□□□□□□□□□□□70□□□□□
2□□□□□□□□
□□□oftern□Express□DHL□TNT□UPS□□□□□□□□□EMS□SPSR□139 Express□

□□□LCL□FCL
□□□