

● SPECIFICATION


Infared 165 XE-165

Specifications:

Display	2.8" Resistive type Touch Panel color LCD screen
Resolution	32 * 32
Total Pixel	1024 pixels
Resolution of Visible image:	0.3 mega pixels.
Temperature Range	-20°C to 1000°C (-4°F to 1907°F)
Measure Accuracy	±2% or ±2°C (±2%±4°F)
FOV/Shortest Focal Length	20× 20/0.5m
Thermal Sensitivity:	0.5°C
Wavelength Range	8-11.5μm
Emissivity	0.1-1.0 Adjustable
Image Capturing Frequency	6HZ
Keys	7 keys(Power,Up/Down/Left/Right,Menu,Measure)
Sensors	32*32 Thermal Array, Humidity Sensor, CMOS sensor
Focus Distance	Fixed
Vision Option	5 kinds of full infrared to the full visual, mixing visible and infrared.
Internal Memory	1GM
External Memory(Micro SD slot)	Up to 64G (Not Included)
USB Connection	Photo upload to PC and USB charging battery
File Format	BMP,JPG
Video Format	MP4
Power Supply	3.7V Li-ion recharged battery,2500mAh,size:18650
Battery Life	6 Hrs
Auto Power-off Time	5 mins
Authentication	CE, RoHS
Blending Mode	Hue blending
Temperature Alert	High or Low Tempe.Alert
Brightness	Adjustable Brighness
Auto off Function	Adjustable Auto-off function
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 60°C
Relative Humidity	10%RH to 80%RH
Package Lists	1 * Thermal Infrared Imager 1 * USB Cable 1 * User Manual 1 * Protection bag

● PRODUCT PICTURES


XE-165

XEAST[®]



XEAST®



XEAST®



XEAST®



XEAST[®]



● **PACKAGE INCLUDE**

XEAST[®]

XEAST[®]



XEAST®



● TERMS OF TRADE

XEAST®

1. 付款条件：
T / T, L / C, Paypal, MoneyGram 或 Western Union 均可。
30 % 预付款 70 % 货到付款

2. 运输条件：
我们提供多种运输方式（DHL, TNT, UPS, FEDEX, EMS, SPSR, 139 Express 等），LCL, FCL
均可。我们可根据客户的需求提供不同的运输方案。

● COMPANY INFORMATION

XEAST®



SALES TEAM



XEAST®
Your Testing Partner



WOKRSHOP

