

HT-02

體積	2.4 公升
尺寸	60 * 60
重量	3600 公克
溫度範圍	0.3 度
溫度範圍	-20 °C ~ 300 °C (-4 °F ~ 572 °F)
溫度精度	± 2 % 或 ± 2 °C (± 4 °F)
FOV / 視野	20 x 20 / 0.5m
溫度	0.5 °C
溫度	8-14µm
溫度	0.1 ~ 1.0 度
溫度	6HZ
溫度	度
溫度	溫度, 溫度, 溫度, 溫度 (溫度) 或 溫度 (溫度)
溫度	5 度
溫度	SD (4G)
溫度	BMP
溫度	溫度 / 溫度 / 溫度
溫度	4 * 1.5V AA 電池
溫度	6 度
溫度	12 度
溫度	CE, RoHS
溫度	-5 °C ~ 40 °C (23 °F ~ 104 °F)
溫度	-20 °C ~ 50 °C (-4 °F ~ 122 °F)
溫度	10 % RH ~ 80 % RH
溫度	21.2 * 9 * 6.2cm / 8.3 * 3.5 * 2.4in
溫度	231.2g / 8.2oz
溫度	27 * 19 * 11cm / 10.6 * 7.5 * 4.3in
溫度	927g / 32.7oz
溫度	1 * 溫度 1 * SD (4G) 1 * 溫度 1 * 溫度 1 * 溫度





● APPLICATIONS

XEAST®

HT02



BBQ



BAKING



REPAIR



CHEMISTRY

Thermal Imager

It is practical, professional, precision and super efficient.



0%




30%



60%



80%



100%



It can turn thermal image into visional image which is quickly find out the problem area.



● PACKAGE INCLUDE

XEAST®

1. 1 x Thermal Imager HT-02







SALES TEAM



WOKRSHOP

