#### • SPECIFICATION

XEAST®

	IP: 54
	3 * 360º
	632nm
	± 3.5 °
H / V Accurancy	1.5mm / 7m
	90 ° ± 30º
	20[].([][]])
	□□ 4x1.5V AA □□□
	II
00 00 0 000 000 :	1 🛮 🖺

PRODUCT PICTURES







□□□□& ensp; apperance.2& □□&□ ensp; of□□□□& □□□, □□□ □□□& ensp; □□.

# Beatiful apperance, the New design, hot selling, we recommend this laser level meter



The bottom of the laser level,it meet CE standards,it can use the 1/4 inch or 5/8 inch thread tripod or stand



The battery details, it can use both lithium battery and AA battery.



□□□□ & Itsp; □□□ & nbsp; □□ & nbsp; AA & ensp; □□□□ □□ □□□□.



□□□ & ensp; □□□ & ensp; □□ & ensp; @ ensp; □□□ & □□□

The details of the laser, each part of the laser level meter



& ensp; || || || & ensp; & ensp; || || & ensp; || & ens

# The button of the panel



& ensp; □□□ & ensp; □□ & ensp;



#### PACKAGE INCLUDE

- 1 \* 000 00
- 1 \* 00 0 00
- 1 \* 00 000
- 1 \* 1.5V AA [][] []
- 1 \* 00 00 000 + EU 000
- 1 \* 000 000
- 1 \* [
- 1 \* [] []
- 1 \* [][]

## XEAST®









#### TERMS OF TRADE

XEAST®

1). | | | | | | |

 $\square\square\square$  T / T, L / C, Paypal, MoneyGram  $\square$  Western Union $\square$   $\square\square\square\square$ .

□□ □□ 30 % □□□ □ □□ **70** % □□.

2). 🔲 🔲 :

**COMPANY INFORMATIONS** 









SALES TEAM







Your Testing Partner





## WOKRSHOP





