

Shenzhen Laesent Technology CO.,LTD



+86-(0)755-82566735



Olivia Cao @laesentbiz.cn

◆ The Leading Supplier of Test & Measurement Instruments

[XEAST XE-S2 50 □. / 70 □. / 100 □. / 120 □.](#)

● SPECIFICATION



□□□	XE-S2	□□□□□□□& subtraction	√
□□□□□	0.2 ~ 50 □□□ / 70/100/120	Angle sensor	√
□□□□□□□□□□	±(2mm + 5 * 10-5Dmm)	□□□□□□□□□□□□	□□□□□□□□□□□□ / □□□□□□ / □□□□
□□□□□□□□□□□□	√	□□□□□□□□	/ □□□□ / □□□□□□ / m + □□
□□□□□□□□□□□□	√	□□□□□□□□□□□□□□□□	30 □□□□
□□□□□□□□□□□□	√	□□□□□□□□□□□□	□□□□□□□□□□ 2.0 □□□□
□□□□□□□□□□□□	√	□□□□□□□□□□□□	□□□□ 2
□□□□□□□□□□	√	□□□□□□□□□□□□	□□□□□□□□□□□□□□
□□□□□□□□□□□□□□ (1)	√	□□□□□□□□□□□□□□	□□□□□□□□□□ AA * 3 (□□□□□□□□□□□□□□ NiMH)
□□□□□□□□□□□□□□ (2)	√	□□□□□□□□□□□□□□□□	0 ~ 40°C
□□□□□□□□□□□□□□	√	□□□□	115 * 49 * 26mm
□□□□□□□□□□□□□□	√		

● PRODUCT PICTURES





Dual power mode

This product adopts dual power supply mode, ordinary dry battery and nickel-metal hydride rechargeable battery. When installing rechargeable battery, it can be directly charged. When installing ordinary dry battery, please do not use USB charging to avoid accidents.



Cycle charging

Nickel-metal hydride rechargeable battery



Emergency battery duration

3*dry battery

XEAST[®]



XEAST®





Electronic angle sensor

When measuring, the angle is displayed in real time, the data is more intuitive, easy to read, and it is easier to find the horizontal direction to meet various measurement requirements.



● TERMS OF TRADE

XEAST®

1) 付款方式:

Trade Assurance, T / T, L / C, Paypal, MoneyGram 或 Western Union

30% 预付款 70% 货到付款

2) 运输方式:

采用 (DHL, TNT, UPS, FEDEX, EMS, SPSR, 139 快递), LCL, FCL

所有数据仅供参考，不作为法律依据。如有变更，恕不另行通知。请留意产品包装上的最新信息。



SALES TEAM



WOKRSHOP

